

APTC-FGQ202X - Splitter Óptico Desbalanceado

1*2 Single Mode

Splitter Date Sheet

Operating Wavelength(nm)	1260-1650	Inspected Date	2018-6-1
P/N	1*2-SM-0.9	Fiber Type	G657A
Connector Type	NO	Fiber Length(m)	1.5
Storage Temperature	-40~+85℃	Operating Temperature	-40~+85℃

Item	IL(dB) FBT30		IL(dB) FBT70		PDL(dB)		RL(dB)	
	1310	1550	1310	1550	1310	1550	1310	1550
Wavelength(nm)	1310	1550	1310	1550	1310	1550	1310	1550
Spec.	MAX 6.3		MAX 2.3		MAX 0.3		≥55	
Port1	5.47	5.63	2.04	1.86	0.19	0.13	Pass	Pass
Port2	5.57	6.01	1.74	1.67	0.01	0.21	Pass	Pass
Input	N/A	N/A	N/A	N/A	N/A	N/A	Pass	Pass
MAX	5.57	6.01	2.04	1.86	0.19	0.21	N/A	
MIN	5.47	5.63	1.74	1.67	0.01	0.13	N/A	
Average	5.52	5.82	1.89	1.77	0.1	0.17	N/A	
Uniformity(≤0.3dB)	0.05	0.19	0.15	0.1	Directivity(dB)		≥55	

Checked by: Chen Bin

QC By: Li Yu Rong

