



SPECIFICATION:

CIRCUIT NO.: SINGLE PORT
 CURRENT RATING : AWG#22=3 AMP
 VOLTAGE RATING: 250V AC, DC
 TOTAL RESISTANCE: 5 mill-Ohm Max.
 TEMPERATURE RANGE: -25°C ~ +85°C
 INSULATOR RESISTANCE : 1000 M ohm Min.
 DIELECTRIC WITHSTANDING : AC 2000 Volts
 TERMINAL LOCKING FORCE: 8Kg Min.

MATERIALS:

INSULATOR MATERIAL : NYLON 94V-2, CLEAR-WHITE
 CONTACT MATERIAL: BRASS, Tin-Plated/Un-Plated
 APPLICATION

ACCEPT QUICK-DISCONNECT TERMINAL: 3301T/3302T SERIES
 ACCEPT CRIMP TERMINAL: 66101T SERIES
 MATED TAB-TERMINAL SIZE: 6.2 / 6.35 mm
 ACCEPT WIRE SIZE: AWG 14 TO AWG 22

CUSTOMER DRAWING

MATERIAL:
 FINISH(COLOR) : NATURE
 FILE NAME:

LANDWIN 聯盈電子股份有限公司
 LANDWIN ELECTRONIC CORP.

SCALE	FREE	SHEET	1 OF 1
DRAWN BY:	<i>adlan</i>	DATE	14/DEC/05
APPROVED BY:	<i>Frank</i>	UNIT	mm
GENERAL TOLERANCE:	(AQ)	REV.	A
ANGLE:	±3°	DRAW NO.	66103S0102
DIM:	±0.5 xxx ±0.25 xxxx ±0.12 xxxx ±0.08	TITLE:	SINGLE PORT HOUSING
REV.	NEW RELEASE	ECN NO.	
REV.	REVISION RECORD	DATE	

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO LANDWIN ELECTRONIC CORP. SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION.